

## Polling Place Inspection Log 2023

Governing Statute 1-3-18. Polling places; building requirements; inspection.

A. The location of each polling place within a building shall be clearly designated by appropriate signs, displayed prominently and clearly. Signs for each polling place shall also be clearly displayed outside the building where polling takes place.

B. Not less than thirty days prior to each election at which a building is intended for use as an alternate voting location, a mobile alternate voting location or an election day polling place, the county clerk or the clerk's designated representative shall physically inspect each such facility to determine its suitability for use as a polling place and its capability of handling heavy voter traffic in the most expeditious manner with a maximum efficiency and minimum discomfort of the voter. The county clerk shall maintain a log of the day and time each facility was physically inspected, whether the inspection was performed by the county clerk, and if the inspection was not performed by the county clerk, the name of the person designated by the county clerk to perform the inspection.

C. Each polling place shall be furnished and have available equipment necessary to assist voters in reading the ballot. History: Laws 1989, ch. 199, § 1; 2011, ch. 131, § 5; 2019, ch. 212, § 43.

Complete all sections. Indicate and describe any usability and accessibility barriers and make general recommendations for overcoming them using space provided at the end. Complete floor plan and site plan as described. Complete signage placement plan for all locations.

Inspection Information				
Inspection Date:		Time:		
Inspector Name(s):				
Inspector Name(s):				
Has staff Inspecting read the 2019 DOJ Settlement Agreement?				

	Polling Place Location Information
Location Name:	
Physical Address:	
City/Town, Zip:	
Suite/Unit Number:	
Mailing Address:	
Email Address:	
Building Owner/ Management Company:	
Building Emergency Contact	
Contact's Name & Title	
Contact Phone/Cell:	
Fax Number:	



Type of Building

	Primary & General	Other
🗆 School Circle Grade: Elem Mid High		
🗆 Tribal Building		
Community Center		
🗆 Governt. Circle Type: County, City, State		
🗆 University		
Private Business Circle Type: W/in Strip Mall		
Stand alone		

General Location Notes: Identify issues/problems associated w/ this location.

1. Major cross streets and landmarks:

2. Street Entrance closest to voting entrance and special instructions:

3. Liquor Establishments within 200 feet? No

This inspection/survey instrument must include measurements and photographs and will also require the identification of appropriate remedial measures, including the remedial measures in paragraph 16 of the DOJ Settlement Agreement. If the polling site cannot be made accessible through remedial measures as outlined in the Settlement agreement and as defined in the survey instrument on election day, the Bureau of Elections will reject the location and continue searching until an accessible location is found.



Inne Dradyomero

Sandoval County Clerk

## ADA PLACE ACCESSIBILITY CHECLIST [ada.gov/votingchecklist.htm] \*Denotes ADA Guide

A P	ARKING*		
	Only complete this section if off-street parking is provided to voters. If street parking is not provided to voters, go to Section B.	Yes / No / NA	Deficiencies / Remedies / Notes
	ore than 25 parking spaces are provided to voters, see the 2010 ndards for the number of accessible parking spaces required. )8.2)		
A1	Is there at least one designated van accessible space with signage with the International Symbol of Accessibility and designated "van accessible"? (§§208.2, 208.2.4, 502.6) Is the bottom of the sign as least 60 inches above the ground?	□Yes □No Measurement:	
A2	Are the designated van accessible spaces at least 96" wide with a 96" wide access aisle, or 132" wide with a 60" wide access aisle? (§§502.2, 502.3) Width of space Width of access aisle	□Yes □No Measurement:	
A3	For van accessible spaces (particularly in a garage or parking structure), is there vertical clearance of at least 98" for the vehicular route to the parking space, in the parking space and access aisle, and along the vehicular route to the exit? (§502.5)	□Yes □No Measurement:	
A4	Are designated accessible parking spaces and the access aisles serving them on a level surface, with slopes not exceeding 1:48 in all directions? (Note: Curb ramps may not be part of an access aisle since they include slopes greater than 1:48.) (§502.4)	□Yes □No Measurement:	
A5	Are the surfaces of the designated accessible parking spaces and access aisles stable, firm, and slip resistant? (§§502.4, 302.1)	□Yes □No Measurement:	
A6	Are the designated accessible parking spaces located on the shortest accessible route to the accessible entrance? (§208.3.1)	□Yes □No Measurement:	

**3** | Page of Polling Place Inspection Log 2021



omero nne Trady-

B P/	B PASSENGER DROP-OFF AREA*					
B. Only complete this section if a passenger drop-off area is provided for		Yes / No / NA	Deficiencies / Remedies / Notes			
vote	ers. If a drop-off area is not provided to voters, go to Section C.		No passenger drop off area at this location			
B1	Is the vehicle pull-up space on a level surface, with slopes not exceeding 1:48 in all directions? (§503.4)	□Yes □No Measurement:				
B2	Is the access aisle next to the vehicle pull-up space on a level surface, with a slope not exceeding 1:48 in all directions? (§503.4)	□Yes □No Measurement:				
B3	Is there vertical clearance of at least 114" (9 feet 6 inches) from the site entrance to the vehicle pull-up area, in the access aisle, and along the vehicular route to the exit? (§503.5)	□Yes □No Measurement:				
B4	Is a curb ramp provided if a curb separates the access aisle from the accessible route to the accessible entrance? (§§206.2.1, 503.3)	□Yes □No Measurement:				
B5	Is the width of the curb ramp surface at least 36" (not counting the side flares)? (§405.5)	□Yes □No Measurement:				
B6	Does an accessible route connect the access aisle and curb ramp to the accessible entrance of the polling place? (§206.2)	□Yes □No Measurement:				



omero nne )rady-

C EX	TERIOR TO ACCESSIBLE ENTRANCE*		
route	omplete a separate Exterior Route form, when applicable, for the s from 1) parking, 2) passenger drop-off areas, 3) public sidewalks 4) public transportation stops.	Yes / No / NA	Deficiencies / Remedies / Notes
Exter	or route location:		
C1	Is the route at least 36" wide? (§403.5.1)	□Yes □No	
C2	Is the route free of abrupt changes in level greater than 1/2", including stairs? (§303)		
C3	Is the route free of surface openings greater than 1/2", such as grates or holes in the pavement? (§302.3)	□Yes □No	
C4	Are walking surfaces stable, firm, and slip resistant? (§302.1)	□Yes □No	
C5	Is the route free of wall mounted objects that protrude more than 4" into the path of travel and are between 27" and 80" high? (§307.2)	□Yes □No	
C6	Is the route free of post mounted objects that protrude more than 12" into the path of travel and are between 27" and 80" high? (§307.3)	□Yes □No	
C7	Are objects that hang over the pedestrian route 80" or higher, including the underside of exterior stairs? (§307.4)		
C8	If the route crosses a curb, is there a curb ramp that is at least 36" wide with a slope no more than 1:12? (§§303.4, 405.2, 405.5, 406.1)		
C9	Is the running slope of part of the route greater than 1:20? If yes, go to Section G. (§402.2)		
C10	Is the cross slope of the accessible route no greater than 1:48? (§§403.3, 405.3)	□Yes □No	



omero nne )rady-

D POLLING PLACE ENTRANCES*			
D		Yes / No / NA	Deficiencies / Remedies / Notes
D1	Is the clear width of the door opening (one door or one active leaf of a double door) at least 32"? (§404.2.3)	□Yes □No	
D2	Is each door hardware useable with one hand, without tight grasping, pinching, or twisting of the wrist? (§§309.4, 404.2.7)		
D3	On the pull side of the door, is there at least 18" of clearance provided to the side of the latch? (§§404.2.4.4, 405.7.1)	□Yes □No	
D4	Is the area in front of the door level, with slopes no greater than 1:48 in all directions? (§§404.2.4.4, 405.7.1)	□Yes □No	
D5	If there are doors in a series, is the distance between the two hinged doors at least 48" plus the width of the door swinging into the space? (§404.2.6)	□Yes □No	
D6	Can the second door (interior door) in the series be opened with no more than 5 pounds of force? (§309.4)	□Yes □No	
D7	Does the second door (interior door) in the series comply with D2, D3, and D4, above?	□Yes □No	
D8	Are door thresholds no higher than 1/2"? (Note: If the threshold is between 1/4" and 1/2" it must be beveled.) (§404.2.5)	□Yes □No	
D9	Do inaccessible entrances have signage directing voters to the accessible entrance? (§216.6)	□Yes □No	
D10	If voters are directed to an alternative accessible entrance, is this entrance kept unlocked during voting hours? (28 C.F.R. §§35.130, 35.133)	□Yes □No	



omero nne )rady-

E ROUTE FROM ENTRANCE INTO VOTING AREA*			
E		Yes / No / NA	Deficiencies / Remedies / Notes
<u></u>			
E1	Is the route at least 36" wide? (§403.5.1)	□Yes □No	
E2	Is the route free of wall mounted objects that protrude more than 4"		
	into the path of travel and are between 27" and 80" high? (§307.2)		
E3	Is the route free of post mounted objects that protrude more than 12"	□Yes □No	
	into the path of travel and are between 27" and 80" high? (§307.3)		
E4	Are objects that hang over the route 80" or higher, including the	□Yes □No	
	underside of stairs? (§307.4)		
E5	Is the route free of abrupt changes in level greater than 1/2", including	□Yes □No	
	stairs? (§303)		
E6	Is the running slope of part of the route greater than 1:20? If yes, go to	□Yes □No	
	Section G. (§ 303.4)		
Ξ7	If the route to the voting area has stairs, is a platform lift or elevator	□Yes □No	
	provided? If yes, go to Section H (lifts) or Section I (elevators). (§402.2)		
<b>E</b> 8	If doors are provided along the route to the voting area, is the clear	□Yes □No	
	width of each door opening (one door or one active leaf of a double		
	door) at least 32"? (§404.2.3)		
E9	Is each door hardware useable with one hand without tight grasping,	□Yes □No	
	pinching, or twisting of the wrist? (§§309.4, 404.2.7)		
E10	Can each door be opened with no more than 5 pounds of force?	□Yes □No	
	(§309.4)		
E11	Is the threshold at each door no higher than1/2"? (Note: If the	□Yes □No	
	threshold is between 1/4" and 1/2" it must be beveled.) (§404.2.5)		
E12	On the pull side of each door, is there at least 18" of clearance	□Yes □No	
	provided to the side of the latch? (§404.2.4)		
E13	Is the area in front of each door level, with	□Yes □No	
	slopes no greater than 1:48 in all directions?		
	(§§404.2.4.4, 405.7.1)		

7 | Page of Polling Place Inspection Log 2021



nne omero )rady-

F WI	F WITHIN THE VOTING AREA*			
F		Yes / No / NA	Deficiencies / Remedies / Notes	
F1	Are floor surfaces stable, firm, and slip resistant? (§302.1)	□Yes □No		
F2	Is the route free of wall mounted objects that protrude more than 4" into the path of travel and are between 27" and 80" high? (§307.2)			
F3	Is the route free of post mounted objects that protrude more than 12" into the path of travel and are between 27" and 80" high? (§307.3)	□Yes □No		
F4	Are objects that hang over the route 80" or higher, including the underside of stairs? (§307.4)	□Yes □No		
F5	Is there enough room to provide a route at least 36" wide to the registration table and voting stations? (§403.5.1)	□Yes □No		
F6	Is there enough room to provide a turning space in front of at least one voting station, such as a circle that is at least 60" in diameter? (§304.3)	□Yes □No		
F7	Is there enough room to provide a turning space in front of at least one accessible voting machine, such as a circle that is at least 60" in diameter? (§304.3)	□Yes □No		



Inne Dradyomero

GR	AMPS*		
F. Complete a separate ramp form for each		Yes / No / NA	Deficiencies / Remedies / Notes
ram	p, whether exterior or interior.		
Ran	p location:		
Gl	Is the running slope of the ramp no greater	□Yes □No	
	than 1:12? (§405.2)		
G2	Is the cross slope of the ramp 1:48 or less? (§405.3)		
G3	Is the rise (height) for any ramp run 30" or less? (§405.6)	□Yes □No	
G4	Is the ramp, measured between handrails, at least 36" wide?	□Yes □No	
	(§405.5)		
G5	Does the ramp have a level landing that is at least 60" long, at the	□Yes □No	
	top and bottom of each ramp section? (§405.7)		
G6	For every 30" of rise, is a level landing at least 60" long provided?	□Yes □No	
07	(§§405.6, 405.7)		
G7	Is a level landing, at least 60" by 60" provided where the ramp	□Yes □No	
	changes direction? (§405.7.4)		
G8	If the rise of the ramp is greater than 6", are handrails provided that	□Yes □No	
	are between 34" and 38" above the ramp surface? (§§405.8,		
<u> </u>	505.4)	Vee Ne	
G9	If the rise of the ramp is greater than 6" and the ramp or landing	□Yes □No	
	has a vertical drop-off on either side of the ramp, is edge		
ı	protection provided? (§405.9)		

9 | Page of Polling Place Inspection Log 2021



Inne Dradyomero

H LI	FTS*		
H.		Yes / No / NA	Deficiencies / Remedies / Notes
H1	Is the lift operational at the time of the survey? (28 C.F.R. §§35.130, 35.133)	□Yes □No	
H2	Is the lift independently operable, or can it be made so during Election Day? (§410.1)		
H3	Is there 30" by 48" of clear floor space within the lift? (§§410.3, 305.3)	□Yes □No	
H4	Are the controls for the lift no higher than 48"? (§§410.5, 309.3, 308)	□Yes □No	
H5	Are the controls useable with one hand without tight grasping, pinching or twisting? (§§410.5, 309.4)	□Yes □No	
H6	Is the clear width of the door opening/gate opening at the end of the lift at least 32"? If a side door/gate is provided, is the clear opening width at least 42"? (§410.6)	□Yes □No	



omero nne rad

I EL	I ELEVATORS*			
Ι.		Yes / No / NA	Deficiencies / Remedies / Notes	
11	Is the elevator car door opening at least 36" wide? (§407.3.6, Table 407.4.1)	□Yes □No		
12	Is there space to maneuver within the elevator car, e.g., 51" deep and 68" wide; OR 80" deep and 54" wide; OR 60" deep and 60" wide? (§407.4.1)			
13	Are hallway elevator call buttons 48" high or lower? (§§407.2.1.1, 308.2, 308.3)	□Yes □No		
14	Are elevator car controls 48" high or lower? (§§407.4.6.1, 308.2, 308.3)	□Yes □No		
15	Does the elevator have visible and audible signals in the hallway to indicate the arrival and direction of the elevator car? (§407.2.2.1)	□Yes □No		
16	Does the elevator have visible and audible signals within the elevator car to indicate the position of the car? (§407.4.8)	□Yes □No		

\*Pages 3 – 11 denotes criteria from mandated by DOJ Settlement Agreement.



-nne Dradyomero

Travel from Street to Voting building			
		Yes / No / NA	Deficiencies / Remedies / Notes
1	Are there more than one entry points from the street to the voting building? Determine best path of usage.		
2	Notated on Ariel Map path of travel being utilized?		
3	Describe which path will be used if more than one option is available and why that path has been selected over others:		

Floor Plan of Site			
Or	n attached floor plan, verify & detail the location of items below		Deficiencies / Remedies / Notes
1	Room Dimensions – Show size & Location of doors on floor plan:	40' x 20'	
2	Locations of electrical outlets shown on floor plan.		
3	Locations of data outlets shown on floor plan.		
4	Lighting switches – Show on floor plan.		
5	Dimensions of voting area – Show on floor plans.		
6	Line formation area – mark area with dotted inside room.		
7	Restrooms: Show on floor plan.		
	In good working condition?		
	ADA compliant?		

12 | Page of Polling Place Inspection Log 2021



omero nne )rady-

Vo	Voting Area – Risk Assessment			
-		Yes / No	Deficiencies / Remedies / Notes	
1	Is electrical equipment free from recognized hazards? (Look for damaged equipment and/or exposed electrical parts).	□Yes □No		
2	Are emergency routes clear of obstructions, unlocked, and functioning properly?	□Yes □No		
3	Does back-up lighting work when tested? (Test for 30 seconds)	□Yes □No		
4	Are exit signs illuminated? (Check self-luminescent exit signs for an expiration date)	□Yes □No		
5	Are fire extinguishers within 75 feet (class A fire risk) of any location in the building? (50 feet class B fire risk).	□Yes □No		
6	Are extinguishers less than 40 pounds wall-mounted so the top of the extinguisher is 3 to 5 feet above the floor?	□Yes □No		
7	List expiration dates of applicable fire extinguishers.	□Yes □No		
8	Are sprinklers, fire hydrants, and fire department inlet connections free of obstructions and obvious damage?			
9	Is the location free of visible structural defects?	□Yes □No		
10	Is the location free of obstacles, trip hazards, lighting problems, or other concerns that may pose a risk to health and safety?	□Yes □No		

13 | Page of Polling Place Inspection Log 2021



Inne Dradyomero

Photo Inventory			
		Completed	Deficiencies / Remedies / Notes
1	Face of the Building most recognized by the public.		
2	Main entrance from each parking lot/from the street into building with		
	voting area.		
3	Main voter entrance to building with voting area from each parking lot		
	showing path of travel. May be more that one shot to show path of travel.		
4	From main entrance to voting location/room showing path of travel. If the		
	path of travel is not direct, a shot from each turn or obstacle.		
5	From the entrance to the voting location/room into the room.		
6	Photo of any special features in the room used for voting.		
7	From the entrance to the voting location/room toward the main entrance		
	to the building to find the way out. May be more that one shot to show		
	path of travel.		

Is there a solution for the deficiencies or an alternate site?

14 | Page of Polling Place Inspection Log 2021



Inne Dradyomero

Sandoval County Clerk

Election Signage			
On	attached map, detail all signage placement, & description from all parking	Completed	Deficiencies / Remedies / Notes
are	areas.		
1	Signage at/near all main entrances to campus/building?		
2	Directional signage near parking area marking path of travel to building		
	entrance?		
3	Signage clearly marking building and building entrance?		
4	No campaigning within 100 feet?		
5	Directional signage in hallways and courtyards "Vote here signs"?		

Additional Notes:

Deficiencies / Remedies / Notes